




ArmorPlast™ 125MS Sheet Construction

1/8" AR-1 Sheet

1/2" Acrylic Attack Side

1/2" Polycarbonate Sheet

Interlayer Bond



ArmorPlast™ 125MS Sheet

MULTI SHOT PROTECTION

ArmorPlast™ 125MS ballistic grade sheet is a 1.250", 4-ply acrylic and polycarbonate laminate that meets UL 752 Level 6 rating for high speed multi-shot 9mm (Uzi) ballistic attack. All ArmorPlast™ products incorporate Polycarbonate Sheet produced for high optical quality in security glazing laminates. Exterior surfaces have a proprietary AR hard coat that facilitates cleaning and resists marring, chemical, and graffiti attack. ArmorPlast™ 125MS sheet has a five (5) year Limited Product Warranty against coating failure, yellowing, and hazing. The terms of the warranty are available upon request.

APPLICATIONS

Government and detention facilities, banks, specialty retailers, 24 hour convenience stores, schools, religious facilities.

TYPICAL PROPERTIES*

PROPERTY	VALUES
GAUGE / TOLERANCE	1.30 IN
WEIGHT	8.1 LBS / SQ FT
SHADING COEFFICIENT	0.98
U-VALUE	0.56
LIGHT TRANSMISSION	78%

*Typical properties are not intended for specification purposes

PRODUCT PERFORMANCE RATINGS

BALLISTIC

UL 752 Level 6 multiple shots from a sub-machine gun, such as a 9mm Uzi, with muzzle energy 540-653 ft-lbs
 Supplementary Shotgun • Supplementary UL test using rifled lead slug with a muzzle energy of 2438-2950 ft-lbs (3306-4000 J) and 00 lead buckshot with a muzzle energy of 2078-2415 ft-lbs (2818-3275 J) from a 12-gauge shotgun

AGENCY INFORMATION

UL File: BP6864 • Combustibility Class CC2
 Miami-Dade NOA #15-1014.01
 Florida Building Code 2014





ArmorPlast™ 125MS Sheet

GLAZING RECOMMENDATIONS

- Structural security framing systems with equal or greater forced entry and/or ballistics ratings as the selected ArmorPlast™ laminate are recommended.
- ArmorPlast™ 125MS must be installed with acrylic ply facing the ballistic attack side.
- ArmorPlast™ laminate should be cut to allow for a minimum of one (1) inch edge engagement in the frame, with sufficient rabbet depth for material expansion (approx. 1/16"/ft.)
- Use wet or dry sealants/gaskets that are compatible with polycarbonate.
- Remove protective masking after glazing operations are completed and before prolonged exposure to direct sunlight, moisture, or high temperature.

STANDARD SHEET SIZE

48" x 96"

PRODUCT SPECIFICATION

ArmorPlast™ polycarbonate and acrylic laminate:

- Four-ply, clear ArmorPlast™ Polycarbonate Sheet constructed as follows:
 - 1/8" AR-1 abrasion resistant surface
 - Polyurethane bonding interlayer
 - 1/2" Polycarbonate Sheet
 - Polyurethane bonding interlayer
 - 1/2" acrylic sheet
 - Polyurethane bonding interlayer
 - 1/8" AR-1 abrasion resistant surface

The manner in which you use and the purpose to which you put and utilize our products, technical assistance, and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance, information, and recommendations to determine to your own satisfaction whether our products, technical assistance, and information are suitable for your intended uses and applications. This application-specific analysis must at least include testing to determine suitability from a technical as well as health, safety, and environmental standpoint. Such testing has not necessarily been done by Riot Glass.

Unless we otherwise agree in writing, all products are sold strictly pursuant to the terms of our standard conditions of sale which are available upon request. All information and technical assistance is given without warranty or guarantee and is subject to change without notice. It is expressly understood and agreed that you assume and hereby expressly release us from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance, and information. Any statement or recommendation not contained herein is unauthorized and shall not bind us. Nothing herein shall be construed as a recommendation to use any product in conflict with any claim of any patent relative to any material or its use. No license is implied or in fact granted under the claims of any patent. With respect to health, safety, and environment precautions, the relevant Safety Data Sheets (SDS) and product labels must be observed prior to working with our products.

Riot Glass, Inc

800.580.2303

17941 Brookshire Lane, Huntington Beach, CA 92647

www.RiotGlass.com

ArmorPlast™ is a trademark of Riot Glass, Inc

