



RIOT GLASS® RG300

Product Specification Sheet

1-1/4" SECURITY GLASS


SPECIFYING AND TECHNICAL DATA

The following layers represent the glass makeup - the specific order of materials used to achieve ballistic and/or forced entry ratings.

COMPONENTS

- Layer 1: 1/8" Heat Strengthened Glass
- Layer 2: .025 Urethane
- Layer 3: 1/8" Polycarbonate
- Layer 4: .025 Urethane
- Layer 5: 3/8" Polycarbonate
- Layer 6: .025 Urethane
- Layer 7: 1/8" Polycarbonate
- Layer 8: .05 Urethane
- Layer 9: 1/4" Heat Strengthened Glass
- Layer 10: .037 Spall Shield

GLASS CLAD LAMINATE RG300



BALLISTIC AND FORCED ENTRY RATING

- U.L. 752 Listed Level 3 & 6 - 9 mm Rifle
- H.P. White TP-0500.02 Level III (Step 25) - Forced Entry
- WMFL Level 1 - 44 mag & 60 minute Physical Attack

PROPERTIES & SPECIFICATIONS

| | |
|----------------------------|----------------|
| U Value | 0.86 |
| Shading Coefficient SGHC | 0.83 0.72 |
| Light Transmission | 67% |
| Thickness | 1.24 ~1-1/4" |
| Weight | 10.7 lbs/sqft |
| Dimentional Tolerance | ASTM C 1349 |

STANDARDS

- ANSI Z971.1984 Safety Glazing Materials for Buildings
- ASTM C 1036 Standard Specifications for Flat Glass
- ASTM C 1172 Standard Specification for Laminated Architectural Flat Glass

RIOT GLASS® RG300 OPTIONS:

- Clear
- Reflective Glass (Applied Film)
- One-Way Mirror (Applied Film)
- Translucent White Interlayer (Frosted Layer)
- Tint (Gray, Bronze, Green, & Blue)
- Wire Glass
- Insulating Units
- Low E

More options available. Please inquire for specific size and thickness availability.

WARRANTY

- 2 (Two) years from date of manufacture

CARING FOR EXPOSED GLASS SURFACES

It is imperative to clean the glazing unit during and after the construction period to maintain optimum performance and aesthetic properties. To clean, use a soft, clean cloth and a mild soap, detergent, or slightly acidic cleaning solution (such as vinegar). Avoid using razor blades which can scratch the glass and exposed polycarbonate layer (no spall makeups). Wipe with a clean, lint-free cloth.

STORAGE

Prior to installation:

Store glass in a cool, dry place away from direct sun exposure. If possible, keep the panels in the original shipping crate to limit exposure to dust, dirt, chemicals, and to avoid accidental impact damage.

Copyright © 2017 Riot Glass™. All rights reserved.

SELLER DISCLAIMS ALL IMPLIED WARRANTIES AND SIMILAR OBLIGATIONS (OTHER THAN GOOD TITLE) INCLUDING BUT NOT LIMITED TO THOSE OF FITNESS FOR A PARTICULAR PURPOSE, AND MERCHANTABILITY, WHETHER OTHERWISE ARISING BY LAW, CUSTOM, USAGE, TRADE PRACTICE, COURSE OF DEALING, OR COURSE OF PERFORMANCE. Buyer acknowledges the installation of the goods must be performed by an authorized dealer and with the correct procedures to achieve any particular purpose or safety result. There are no warranties which extend beyond those express warranties contained in the purchase agreement between Buyer and Seller. Any design provided by Seller is based on information provided by Buyer.

