

FORCED ENTRY
CONTAINMENT
LIGHT BALLISTIC

AP-Series

AP375-BR-IGU

Security, Light BR
Insulated Glass Units



PRODUCT DESCRIPTION

AP-Series Security IG Units are available in various configurations:

- AP-Series Security panels on both sides.
- AP-Series Security panels on the exterior/attack side with high performance glass options in the interior/safe side.

All units include our patented "Shock-Spacer" designed to absorb high levels of energy from attack.

The interior glass options include UV and tinted coatings, tempered, and frosted treatments with the added benefit of interior signage and window graphics compatibility.

Designed to fit our Universal Framing System (UFS) but also compatible with all 1.00" glass pocket storefronts.



SECURITY & CONTAINMENT GLAZING IGUs

AP-Series AP375-BR light ballistic and containment grade sheets are abrasion and UV resistant security panels that offer glass-like surface hardness coupled with the impact strength of polycarbonate.

All AP-Series polycarbonate products are engineered for high optical clarity. Interior and exterior surfaces have a proprietary AR hard coat that facilitates cleaning and resists marring, chemical attack, and graffiti.

AP375-BR-IGUs are flexibly-configured to meet your application needs, with annealed teglass, tempered glass, UV-coated glass, or AP25 panels available on the safe-side.

AP375-BR-IGU products have a seven (7) year Limited Product Warranty.

TYPICAL PROPERTIES

Make-up: **3/8" AP375-BR Polycarbonate - 3/8" Spacer - 1/4" Tempered Panel**

THICKNESS	1.00" ± 5%	SHADING COEFFICIENT*	0.687
WEIGHT	5.7 LBS/SQ FT	LIGHT TRANSMISSION*	68.3%
		U-VALUE*	0.449

RATINGS

FORCED ENTRY & CONTAINMENT WITH UNIVERASL FRAMING SYSTEM (UFS)

- ASTM F 1233-08 Class 2.8
- ASTM F 1915 Grade 2
- H.P. White TP 0500 Level 1 Seq 15
- UL972: Burglary Resistant Glazing
- Materials

BALLISTICS

- HPW-TP 0500.03, LEVEL A
- ASTM F 1233, Class HG1.38 Special LRN

COMPLIANCE CERTS

- ANSI Z97.1 Safety Glazing
- CPSC 16 CFR 1201 CAT I and II
- UL 746C: Sustainability for Outdoor Use
- AAMA 501.8: Resistance to Human Impact
- UL 94: Flammability
- UL 94 Propane Torch Test

* Testing conducted on monolithic sheets, not on IGU form; values may vary based on glass makeup.

v.051426

AP-Series Polycarbonate Security IGUs

GLAZING RECOMMENDATIONS

- Structural security framing systems with equal or greater forced entry and/or ballistics ratings to theselected AP-Series security are recommended.
- AP-Series panels should be sized to allow for a minimum of one 3/4” edge engagement in the frame.
- Use wet or dry sealants compatible polycarbonates.
- Remove protective masking after glazing operations are completed and before prolonged exposure todirect sunlight, moisture or high temperature.

SIZES

SAFE-SIDE (Tempered Glass)

1/4" Clear	1/4" Climaguard SN68
1/4" Bronze	SNX62/27 SNX5123
1/4" Low-e	SN68
3/16" Solarban 90	Ultra Clear
Solarban 60	
Solarban 70	

THREAT-SIDE (AP375)

3/8" AP375-BR
Clear Ballistic Polycarbonate

Note: Guardian, Cardinal, and other hardcoat UV coat-
ings or substitutes also available for safe-side glazing.

SELLER DISCLAIMS ALL IMPLIED WARRANTIES AND SIMILAR OBLIGATIONS (OTHER THAN GOOD TITLE) INCLUDING BUT NOT LIMITED TO THOSE OF FITNESS FOR A PARTICULAR PURPOSE, AND MERCHANTABILITY, WHETHER OTHERWISE ARISING BY LAW, CUSTOM, USAGE, TRADE PRACTICE, COURSE OF DEALING, OR COURSE OF PERFORMANCE. Buyer acknowledges the installation of the goods must be performed by an authorized dealer and with the correct procedures to achieve any particular purpose or safety result. There are no warranties which extend beyond those express warranties contained in the purchase agreement between Buyer and Seller. Buyer affirms that it has not relied upon Seller’s skill nor judgment to select or furnish the Goods for any particular purpose beyond the specific express warranties in the Agreement. Any design provided by Seller is based on information provided by Buyer. Seller does not warrant the Goods will comply with the requirements of any safety or environmental code or regulation of any federal, state, municipality or other jurisdiction beyond the specific express warranties or test data in the Agreement.

Buyer acknowledges although components of the Riot Glass, LLC products may contain specific ratings, including ballistics-grade products, such tests were performed in laboratory conditions, in a controlled environment, and only related as a specific component of the overall system. Buyer acknowledges Buyer is purchasing an installed system comprising of multiple components which have been rated, tested, or approved for varying performance levels including ballistics, or fitness of a particular purpose, including but not limited to preventing intrusion by any or limited means. Furthermore, neither Riot Glass, LLC nor its Authorized Dealers can guarantee the installed system will provide the necessary protection to Buyer’s property due to the variance of the environment from laboratory conditions. Riot Glass, LLC specifically disclaims any implied warranties, including fitness for a particular purpose and merchantability, and advises Buyer to conduct its own research to determine the best solution for Buyer’s unique situation.

